

SECTION I - SCHEDULE OF LIGHTING FITTINGS

ITEM	LIGHTING FITTING	DESCRIPTION <i>(Lighting Fittings to be complete with all gears and accessories)</i>
1.	Type 1	600x600mm 45W 4200Lumen, 6000K, over 30,000Hours lamp life, backlit (panel) LED luminaire of full box welded monolithic seamless steel construction with post coat powder paint finish for laying installation, with acrylic micro prism and dispersal diffuser combination and high efficiency LED modules and as Eaton's Taliska Range Cat No. TALP66424KZ or Philips, or Thorn or Approved equivalent.
2.	Type 2	Recessed LED backlit downlight 20W 2000Lumen 6000K over 30,000Hours lamp life luminaire with HF electronic control gear spectacular reflector and as THORN Cruz LED c/w CHALICE 190 GLASS IP44 or LIPER Lip. Led Cob Recessed D/lighter 20w cat No. LPDL20C01-DL or approved equivalent
3.	Type 3	1500mmx300mm 50W 4500Lumen 6000K over 30,000Hours lamp life LED IP65 fully polycarbonate weather resistant and corrosion proof surface mounted luminaire with High Frequency Electronic Control Gear and as Thorn Aqua force LUZP236 or FITZGERALD Cat No. PCW236/HF or approved equivalent.
4.	Type 4	1200mm 20W 2200Lumen 6000K over 30,000Hours lamp life LED mirror light for horizontal mounting to IP65 fully polycarbonate weather resistant and corrosion proof with acrylic diffuser with High Frequency Electronic Control Gear and as Philips, Thorn or approved equivalent.
5.	Type 5	Clear shave single ended LED mirror luminaire for horizontal mounting with a 11W warm white single ended LED tube and with a pull switch incorporated as MK or Thorn or approved equivalent.
6.	Type 6	1200mm 40W 3700Lumen 6000K over 30,000Hours lamp life LED IP65 fully polycarbonate weather resistant and corrosion proof surface mounted luminaire with High Frequency Electronic Control Gear and as Thorn Aqua force LUZP236 or FITZGERALD Cat No. PCW236/HF or approved equivalent.
7.	Type 7	Surface LED downlight 20W 2000Lumen 6000K over 30,000Hours lamp life luminaire with HF electronic control gear spectacular reflector and as THORN Cruz LED c/w CHALICE 190 GLASS IP44 or LIPER Lip.led Cob Surface D/lighter 20w cat No. LPDL20C01-DL or approved equivalent.
8.	Type 8	31W 2500Lumens 6000K over 30,000Hours lamp life adjustable spot light made of die-cast aluminium with cooling fins and complete with tempered shock and heat resistant 4mm thick glass to IP66 and as DisanoElfo 1515 Elfo SLE - wide beam or Approved equivalent.
9.	Type 9	Decorative outdoor corrosion resistant wall luminaire Constructed of rust proof die cast steel body in a grey finish complete with white satinated/ tempered glass shade to IP65 and 16W LED lamp

ITEM	LIGHTING FITTING	DESCRIPTION <i>(Lighting Fittings to be complete with all gears and accessories)</i>
		and as EGLO Park or Philips Cleveland wall bulkhead or Thorn or approved equivalent.
10.	Type 10	1200mm x30mm x40mm (LxWxH) Linear LED strip profile lamp for the counter and reception desk lighting complete with acrylic diffuser and as Osram LEDVANCE Polybar or approved equivalent
11.	Type 11	50W High Powered LED luminaire with 5000Lm 6000K lighting output, over 30,000Hours lamp life, wall mounted, corrosion proof floodlight Luminaire to IP65 complete with reflector electronic control gear and lamp and As Massive, Micromark or Thorn or approved equivalent.
12.	Type 12	Bulkhead fitting constructed with die cast aluminium with opal glass shade and wire gauze to IP66 complete with 10W LED lamp and as Thorn or approved equivalent
13.	Type 13	Decorative 715x1100mm (LxH) pendant made of stainless steel body and white pleated shade complete with 2x12W LED and as EGLO Fortuna, Micromark or Thorn or approved equivalent.
14.	Type 14	Decorative wall luminaire made of stainless steel body and white pleated shade complete with 12W LED lamp and as EGLO Fortuna, Micromark or Thorn or approved equivalent.
15.	Type 15	100W High Powered LED luminaire with 10000Lm 6000K lighting output, over 30,000Hours lamp life, wall mounted, corrosion proof floodlight Luminaire to IP65 complete with reflector electronic control gear and lamp and As Massive, Micromark or Thorn or approved equivalent.
16.	Type P	Safety pendant consisting of a ceiling rose pendant lamp holder and a 300mm long twin core circular heat resistant cord for 11W energy saving lamp and as MK Cat No 1189W05 or approved equivalent.
17.	Type 17	1200mm 25W 2200Lumen 6000K over 30,000Hours lamp life LED mirror light for horizontal mounting to IP65 fully polycarbonate weather resistant and corrosion proof with acrylic diffuser with High Frequency Electronic Control Gear and as Philips, Thorn or approved equivalent